



**5059-23
Pilot Relite Control**

PILOT RELITE CONTROLS 5059 AND 5059A

Generates Spark Until a Pilot Flame is Sensed

FEATURES

- Generates spark pulse until flame is sensed through spark electrode.
- Begins sparking immediately if flame extinguishes.
- Rugged solid state module design.
- Available in 24 and 120 volt input.
- Spark plug or spike output configurations available.

SPECIFICATIONS

Agency A.G.A. design certified and C.G.A. certified

Model Number	Input Voltage	Electrical Rating	Description
5059-23	24 VAC	0.03 amps	Spark plug and 1/4" spade connectors
5059-134	24 VAC	0.03 amps	Spike connector
5059A-21	120 VAC	0.04 amps	Spark plug and 1/4" spade connectors
5059-25	24 VAC	0.03 amps	Spark plug and 1/4" spade connectors



50A22-4

**COMBINATION RELITE CONTROL AND
LOCKOUT TIMER: MODEL 50A22**

Combines in One Enclosure the Functions of a 5059 Type and 5022 Control

FEATURES

- Includes all the features of a 5059 Relite Control.
- Lockout timer opens circuit if flame is not sensed in ignition period.
- Replaces previous 5022 timers.

SPECIFICATIONS

Agency A.G.A. design certified and C.G.A. certified



50A22-201

Model Number	Input Voltage	Electrical Rating	Description
50A22-4	24 VAC	0.11 amps	5 wire edge connector
50A22-21	24 VAC	0.11 amps	6 male spade connections, 1/4"
50A22-201	24 VAC	0.11 amps	5 wire edge connector used with edge connect gas valves. Spark plug or 1/4" spade connectors



760-56

IGNITION ELECTRODE ASSEMBLIES

Use Type 760-56 to Replace Cycle-Pilot® Ignition Electrodes and Cable Assemblies

Model Number	Description
760-56	24" lead with slip on bracket. Also includes perforated mounting strap for varying applications
760-310	Same as 760-56 except with universal mounting bracket

* Indicates Canadian Model Number: call 1-800-305-6953 to order